

SCIENTIFIC REPORTS

OPEN

Corrigendum: nanoSQUID operation using kinetic rather than magnetic induction

Adam N. McCaughan, Qingyuan Zhao & Karl K. Berggren

Scientific Reports 6:28095; doi: 10.1038/srep28095; published online 14 June 2016; updated on 12 January 2017

The authors neglected to cite previous studies related to the use of current injection as a viable means to control SQUIDs. These additional references are listed below as references 1, 2 and 3 and should appear in the Introduction section as below.

“Current injection has been demonstrated before as a viable means to control SQUIDs^{12–14} dominated by geometric inductance. These directly-coupled SQUIDs used a large pickup loop to convert an applied magnetic field into a current bias which was injected a smaller, more sensitive readout SQUID. Although the readout SQUIDs in these devices were smaller than the pickup loops, they still used large geometric inductors to route the injected current”.

should read:

“Current injection has been demonstrated before as a viable means to control SQUIDs^{1–3,12–14} dominated either by geometric or kinetic inductances. Several of these implementations used a large pickup loop to convert an applied magnetic field into a current bias which was injected into a smaller, more sensitive readout SQUID”.

In addition, the authors would like to alert readers to a similar result published prior to final acceptance of this paper. This is listed below as reference 4.

References

1. T. Aomine, K. Mizuno, K. Miyake, K. Matsuo, S. Kusunoki & M. Hidaka. Effects of Magnetic Field and Injected Current on DC SQUIDs with Dayem Bridges. *Jpn. J. Appl. Phys.* **20**, 1311 (1981).
2. H. Terai, M. Hidaka, T. Satoh & S. Tahara. Direct-injection high-Tc Dc-SQUID with an upper YBa₂Cu₃O_{7-x} ground plane. *Appl. Phys. Lett.* **70**, 2690–2692 (1997).
3. J. Johansson, K. Cedergren, T. Bauch & F. Lombardi. Properties of inductance and magnetic penetration depth in (103)-oriented YBa₂Cu₃O_{7-δ} thin films. *Phys. Rev. B* **79**, 1–6 (2009).
4. M. Arzeo, R. Arpaia, R. Baghdadi, F. Lombardi & T. Bauch. Toward ultra high magnetic field sensitivity YBa₂Cu₃O_{7-δ} nanowire based superconducting quantum interference devices. *J. Appl. Phys.* **119**, 174501 (2016).



This work is licensed under a Creative Commons Attribution 4.0 International License. The images or other third party material in this article are included in the article’s Creative Commons license, unless indicated otherwise in the credit line; if the material is not included under the Creative Commons license, users will need to obtain permission from the license holder to reproduce the material. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/>

© The Author(s) 2017